

# TSX Series High-Performance Pharmacy Refrigerators



Vaccines and medications



Clinical applications



Diagnostics kits and reagents



Our high-performance pharmacy refrigerators feature adjustable basket drawers and glass doors for the easy identification and access of vaccines, pharmaceuticals, chemotherapeutics and other material requiring 2 to 8°C storage.

- Heat-free defrost for maximum temperature uniformity
- Convenient, fully extendable and adjustable basket drawers
- GMP Clean Room Class A / ISO 6 (ISO EN 14644-1) compatible with appropriate pre-install preparation
- Four 2" casters for easy mobility; the front two are lockable
- Bright, LED interior lighting
- Self-closing door with 90° stop to assist with inventory loads
- See pages 14–21 for options and accessories



Thermo Scientific™  
TSX 650 liter  
pharmacy refrigerator

## TSX Series high-performance pharmacy refrigerators

Model no.	Temp. range (setpoint)	Capacity cu. ft. (liters)	Electrical (plug)	Basket Doors	Basket Drawers	Defrost	Certification	Interior dimensions D x W x H in. (cm)	Exterior dimensions D x W x H in. (cm)	Shipping weight lbs. (kg)
TSX1205PY			115V, 60Hz (NEMA 5-15)							388 (176)
TSX1205PZ	3–7°C (5°C)	11.5 (326)	208-230V, 60Hz (NEMA 6-15)	1 glass	5	auto	CE, cUL	21.8 x 20.0 x 52.4 (55.4 x 50.8 x 133.1)	30.5 x 24.0 x 73.0 (77.5 x 61.9 x 185.4)	388 (176)
TSX1205PV			208-230V, 50Hz (CEE 7/7)							388 (176)
TSX2305PY			115V, 60Hz (NEMA 5-15)							531 (241)
TSX2305PZ	3–7°C (5°C)	23 (650)	208-230V, 50/60Hz (NEMA 6-15)	1 glass	6	auto	CE, cUL	28.5 x 24.0 x 58.0 (72.3 x 61.0 x 147.3)	37.8 x 28.0 x 78.5 (96.0 x 71.1 x 199.4)	510 (231)
TSX2305PV			208-230V, 50Hz (CEE 7/7)							510 (231)
TSX3005PY			115V, 60Hz (NEMA 5-15)							541 (245)
TSX3005PZ	3–7°C (5°C)	29.2 (827)	208-230V, 60Hz (NEMA 6-15)	1 glass	6	auto	CE, cUL	28.5 x 30.0 x 58.0 (72.3 x 76.2 x 147.3)	37.3 x 34.0 x 78.5 (94.7 x 86.4 x 199.4)	541 (245)
TSX3005PV			208-230V, 50Hz (CEE 7/7)							541 (245)
TSX5005PY			115V, 60Hz (NEMA 5-15)							830 (376)
TSX5005PZ	3–7°C (5°C)	51.1 (1447)	208-230V, 60Hz (NEMA 6-15)	2 glass	12	auto	CE, cUL	28.5 x 52.5 x 58.0 (72.4 x 133.4 x 147.3)	37.8 x 56.5 x 78.5 (96.0 x 143.5 x 199.4)	830 (376)
TSX5005PV			208-230V, 50Hz (CEE 7/7)							830 (376)